

RoughDeck® SLV



RICE LAKE®
WEIGHING SYSTEMS

800-472-6703


www.ricelake.com

RoughDeck® SLV

The SLV offers the rugged and durable features of a RoughDeck floor scale modified to meet the demands of livestock weighing. The diamond tread plate and rigid structural steel channel frame provide durability for weighing sheep, goats, cattle, hogs, horses and more. The SLV can be customized for retrofit or unique applications.

Accuracy requires a specialized foot

Adjustable SUREFOOT™ support feet incorporate stainless steel top plates and neoprene bases. This unique combination decreases extraneous forces on the load cell, resulting in superior accuracy and repeatability.



482 Legend™ Series

The 482 Legend™ Series digital weight indicator is engineered for reliable performance on any ranch or farm. Engineered to handle the unique requirements of livestock weighing, the 482 measures individual animals and displays weight with its bright and readable backlit LCD display.

A NEMA Type 4X, stainless steel enclosure offers protection in demanding, sometimes wet or dirty conditions. Combine the 482 with a printer to easily and efficiently keep track of animal weight readouts. This digital livestock indicator can be used in Legal for Trade weighing applications.



STANDARD FEATURES

- Mild steel construction
- Diamond safety tread plate deck
- Rigid type structural steel channel frame
- NEMA Type 4X, stainless steel side-access junction box without quick connector
- Signal trim summing board
- Four adjustable stainless steel SUREFOOT™ support feet
- 20 ft SURVIVOR™ EL147HE hostile environment load cell cable
- Four alloy steel load cells

OPTIONS

- Smooth deck
- Stainless steel load cells (RL32018S IP66) and hardware
- Stainless steel hermetically sealed load cells (RL32218S-HE IP69K) and hardware
- Angle iron bolted to scale for wood deck provisions
(note: wood to be supplied by customer)

SPECIFICATIONS

END LOAD CAPACITY:	125% full scale
CABLE LENGTH:	20 ft (6 m)
CAPACITY:	Not to exceed 4,000 x 1 lb (32 square feet) 3 ft x 8 ft: 4,000 lb increments 4 ft x 8 ft: 4,000 lb increments
APPROVALS:	NTEP CC 92-001 Class III 4,000 d
WARRANTY:	Two-year warranty



Drawing is representation of PN 124193 SLV scale

Drawing is representation of PN 160100 SLV scale

SALES AND TECHNICAL ASSISTANCE

RICE LAKE
WEIGHING SYSTEMS

HEADQUARTERS

230 West Coleman Street
Rice Lake, Wisconsin 54868 - USA
Tel: (715) 234 9171 | Fax: (715) 234 6967
www.ricelake.com